

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

UFI: 7MNP-C0Y7-6P00-YQVW

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: SORMAT Oy
 Street: Harjutie 5
 Place: FIN-21290 Rusko
 Telephone: +358 207 940 200
 e-mail: sormat@sormat.com
 Internet: www.sormat.com
 Responsible Department: Technical information: sormat@sormat.com

1.4. Emergency telephone number:

Poison Information Center and Clinical Toxicology, Mainz Tel.: +49 (0) 6131 19240 (in English)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
 Serious eye damage/eye irritation: Eye Irrit. 2
 Respiratory or skin sensitisation: Skin Sens. 1
 Specific target organ toxicity - single exposure: STOT SE 3
 Hazard Statements:
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 May cause respiratory irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Methacrylic acid, monoester with propane-1,2-diol;
 Ethylene dimethacrylate

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

Precautionary statements

P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 2 of 11

- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.

Additional advice on labelling

- For distribution to the general public (consumers) additionally indicate voluntarily:
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of the reach of children.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			15 - < 20 %
	248-666-3		01-2119490226-37	
	Eye Irrit. 2, Skin Sens. 1; H319 H317			
97-90-5	Ethylene dimethacrylate			10 - < 15 %
	202-617-2	607-114-00-5	01-2119965172-38	
	Skin Sens. 1, STOT SE 3; H317 H335			
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol			1 - < 5 %
	254-075-1		01-2119980937-17	
	Acute Tox. 2, Aquatic Chronic 3; H300 H412			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

- May cause an allergic skin reaction.
- Causes serious eye irritation.
- May cause respiratory irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 3 of 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam.
Extinguishing powder
Water spray jet
Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic
Carbon monoxide

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand
Treat the recovered material as prescribed in the section on waste disposal.
Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.
Wear personal protection equipment (refer to section 8).
Avoid contact with skin, eyes and clothes.
When using do not eat, drink or smoke.
Wash hands thoroughly after handling.
Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 4 of 11

Requirements for storage rooms and vessels

- Keep container tightly closed.
- Store in a place accessible by authorized persons only.
- Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

- Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: -20 - +25°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
Worker DNEL, long-term		inhalation	systemic	14,7 mg/m ³
Worker DNEL, long-term		dermal	systemic	4,2 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	8,8 mg/m ³
Consumer DNEL, long-term		dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	2,5 mg/kg bw/day
97-90-5	Ethylene dimethacrylate			
Worker DNEL, long-term		inhalation	systemic	2,45 mg/m ³
Worker DNEL, long-term		dermal	systemic	1,3 mg/kg bw/day

PNEC values

CAS No	Substance	Environmental compartment	Value
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol		
Freshwater			0,904 mg/l
Marine water			0,904 mg/l
Freshwater sediment			6,28 mg/kg
Marine sediment			6,28 mg/kg
Micro-organisms in sewage treatment plants (STP)			10 mg/l
Soil			0,727 mg/kg
97-90-5	Ethylene dimethacrylate		
Freshwater			0,139 mg/l
Marine water			0,014 mg/l
Marine water (intermittent releases)			0,15 mg/l
Freshwater sediment			1,6 mg/kg
Marine sediment			0,16 mg/kg
Micro-organisms in sewage treatment plants (STP)			57 mg/l
Soil			0,239 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 5 of 11

Additional advice on limit values

This mixture includes quartz (silica) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

Eye/face protection

Wear eye protection/face protection. Wear safety glasses.

Hand protection

Disposable gloves
 Recommended material: NBR (Nitrile rubber)
 Breakthrough time: > 480 min
 Thickness of the glove material: > 0,2 mm
 DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste	
Colour:	light beige	
pH-Value:		not determined
Changes in the physical state		
Melting point:		not determined
Initial boiling point and boiling range:		not determined
Flash point:		not applicable
Flammability		
Solid:		not determined
Gas:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Auto-ignition temperature		
Solid:		not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 6 of 11

Gas: not applicable
Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 1,54 g/cm³

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
97-90-5	Ethylene dimethacrylate				
	oral	LD50 8700 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol				
	oral	LD50 27,5 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Methacrylic acid, monoester with propane-1,2-diol; Ethylene dimethacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Ethylene dimethacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol					
	Acute algae toxicity	ErC50 > 97,2 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 > 143 mg/l	48 h	Daphnia magna (Big water flea)		
	Algae toxicity	NOEC mg/l				
97-90-5	Ethylene dimethacrylate					
	Acute fish toxicity	LC50 15,95 mg/l	96 h	Brachydanio rerio (zebra-fish)		
	Acute algae toxicity	ErC50 17,3 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 44,9 mg/l	48 h	Daphnia magna (Big water flea)		
	Crustacea toxicity	NOEC 13,2 mg/l	2 d			
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol					
	Acute fish toxicity	LC50 17 mg/l	96 h	Brachydanio rerio (zebra-fish)		
	Acute algae toxicity	ErC50 245 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 28,8 mg/l	48 h	Daphnia magna (Big water flea)		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
	OECD 301C	81%	28	
97-90-5	Ethylene dimethacrylate			
	OECD 301D	71 %	28	

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	0,97
97-90-5	Ethylene dimethacrylate	2,4
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	2,1

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 9 of 11

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- 14.4. Packing group:** No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- 14.4. Packing group:** No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- 14.4. Packing group:** No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 10 of 11

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):

Additional information

VOC content: 13,0 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.1 (UFI).

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

ErC50: EC50 in terms of reduction of growth rate

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic

vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. A

Revision date: 23.03.2020

Page 11 of 11

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)
 VOC: Volatile organic compound
 Aquatic Chronic 3: Long-term aquatic hazard, Category 3
 Acute Tox. 2: Acute toxicity, Category 2
 Eye Dam. 1: Serious eye damage/eye irritation, Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2
 Skin Sens. 1: Skin sensitization, Category 1
 STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H300 Fatal if swallowed.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

Revision date: 23.03.2020

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

UFI: QQNP-V0NM-GP0H-M2FY

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: SORMAT Oy
Street: Harjutie 5
Place: FIN-21290 Rusko
Telephone: +358 207 940 200
e-mail: sormat@sormat.com
Internet: www.sormat.com
Responsible Department: Technical information: sormat@sormat.com

1.4. Emergency telephone number:

Poison Information Center and Clinical Toxicology, Mainz Tel.: +49 (0) 6131 19240 (in English)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

Causes serious eye irritation.

May cause an allergic skin reaction.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Dibenzoyl peroxide

Signal word: Warning**Pictograms:****Hazard statements**

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

Revision date: 23.03.2020

Page 2 of 10

Additional advice on labelling

For distribution to the general public (consumers) additionally indicate voluntarily:
 P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of the reach of children.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
94-36-0	Dibenzoyl peroxide			10 - < 15 %
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1 (M-Factor = 10); H241 H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Further Information

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.
 Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

Revision date: 23.03.2020

Page 3 of 10

Extinguishing powder
Water spray jet
Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic
Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand
Treat the recovered material as prescribed in the section on waste disposal.
Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.
Wear personal protection equipment (refer to section 8).
Avoid contact with skin, eyes and clothes.
When using do not eat, drink or smoke.
Wash hands thoroughly after handling.
Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.
Store in a place accessible by authorized persons only.
Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong
Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

Keep container tightly closed in a cool place.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

Revision date: 23.03.2020

Page 4 of 10

storage temperature: 5 - 25°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
94-36-0	Dibenzoyl peroxide			
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	13,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	39 mg/m ³

PNEC values

CAS No	Substance	Value
94-36-0	Dibenzoyl peroxide	
Freshwater		0,00002 mg/l
Marine water		0,000002 mg/l
Freshwater sediment		0,013 mg/kg
Marine sediment		0,001 mg/kg

Additional advice on limit values

This mixture includes quartz (silica) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat or drink.

Eye/face protection

Wear safety glasses.

Hand protection

Disposable gloves

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

Revision date: 23.03.2020

Page 5 of 10

Recommended material: NBR (Nitrile rubber)
 Breakthrough time: > 480 min
 Thickness of the glove material: > 0,2 mm
 DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste	
Colour:	black	
Odour:	characteristic	
pH-Value:		not applicable

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	not applicable

Flammability

Solid:	not determined
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

Auto-ignition temperature

Solid:	not determined
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidising.
 Available oxygen content (%) < 1%
 no classification

Vapour pressure:	not determined
Density (at 20 °C):	1,59 g/cm ³
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined	
Partition coefficient:	not determined
Vapour density:	not determined
Evaporation rate:	not determined

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

Revision date: 23.03.2020

Page 6 of 10

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

Benzoic acid
Benzene
Biphenyl

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
94-36-0	Dibenzoyl peroxide				
	oral	LD50 > 5000 mg/kg	Rat		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Dibenzoyl peroxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

Revision date: 23.03.2020

Page 7 of 10

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus)

IC10: (0 - 72 h) = 30 mg/l

IC50: (0 - 72 h) = 150 mg/l

OECD 202 (Daphnia magna)

EC0/NOEC (48h) = 100 mg/l

EC50 (48h) = >500 mg/l

EC100 (48h) = >>500 mg/l

OECD 203 (Danio rerio)

LC0/NOEC : 250 mg/l

LC50 : > 500 mg/l

LC100 : >> 500 mg/l

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
94-36-0	Dibenzoyl peroxide					
	Acute fish toxicity	LC50 mg/l	0,0602	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50 mg/l	0,0711	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50	0,11 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202
	Algae toxicity	NOEC mg/l	0,02	3 d	Pseudokirchneriella subcapitata	OECD 201
	Crustacea toxicity	NOEC mg/l	0,001	21 d	Daphnia magna (Big water flea)	OECD 211
	Acute bacteria toxicity	(35 mg/l)		0,5 h		OECD 209

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

Revision date: 23.03.2020

Page 8 of 10

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- 14.4. Packing group:** No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- 14.4. Packing group:** No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- 14.4. Packing group:** No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

Revision date: 23.03.2020

Page 9 of 10

- 14.1. UN number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- 14.4. Packing group:** No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):

Additional information

VOC content: 4,3 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

- Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
- Water contaminating class (D): 1 - slightly water contaminating
- Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.1 (UFI).

Abbreviations and acronyms

- ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
- ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- CAS: Chemical Abstracts Service
- CLP: Classification, Labeling and Packaging
- DMEL: Derived Minimal Effect level
- DNEL: Derived No Effect Level
- EC50: Effective concentration, 50%
- IATA: International Air Transport Association
- IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)
- ICAO: International Civil Aviation Organization
- IC50: Inhibitory concentration, 50%
- IMDG: International Maritime Code for Dangerous Goods
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%
- NOEC: No Observed Effect Concentration
- OECD: Organisation for Economic Co-operation and Development

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-Wi Winter resin (ITH 300 Wi (9640072947), ITH 410 Wi (9640072911)), Comp. B

Revision date: 23.03.2020

Page 10 of 10

PBT: persistent, bioaccumulative and toxic
 vPvB: very persistent and very bioaccumulative
 PNEC: Predicted No Effect Concentration
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)
 VOC: Volatile organic compound
 Aquatic Acute 1: Acute aquatic hazard, Category 1
 Aquatic Chronic 1: Long-term aquatic hazard, Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2
 Skin Sens. 1: Skin sensitization, Category 1
 Org. Perox. B: Organic Peroxides, Type B

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H241 Heating may cause a fire or explosion.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)